

SZ-80-36MF

Warranty

- ◆ 2 years Manufacturer Warranty
- ◆ Warranty on Electrical Performance:
5 years 80% of power output.

Manufacturing

- ◆ Original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing.
- ◆ Comprehensive module power testing.

Performance

- ◆ Upgraded module efficiency and portability.
- ◆ Weakened hot-spot effect, lower module failure rate and increased stability by shingle-tech.
- ◆ Optimized performance under low light conditions.
- ◆ Unique cell connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- ◆ USB&DC outputs.

Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C

Nominal Power	80W
Cell Type	Monocrystalline
Module Efficiency	16.21%
Maximum Power Current (Impp)	4.28A
Maximum Power Voltage (Vmpp)	18.70V
Open-circuit Voltage (Voc)	22.10V
Short-circuit Current (Isc)	4.79A
Surface Material	PET
Output Tolerance	±3%
DC Connector Type	MC4
Working Temperature	-40°C~+80°C

Packaging

Folded Dimensions	560*565*30(mm)
Expanded Dimensions	1120*565*3(mm)
Module Weight	2.9kg
Pieces per Pallet	Free
Gross Weight per Pallet	Free
Pallet Dimensions	Free



FRONT



BACK



UNFOLDED



JUNCTION BOX

SOLMAX NEW ENERGY B.V.

Address: Zonnebaan 23, 3542 EB Utrecht, the Netherlands
Tel: +31-307855708
Email: info@solarfam.nl

