

SZ-20-32M

Warranty


- ♦ 5 years Manufacturer Warranty
- ♦ Warranty on Electrical Performance : 10 years 90%
+ 25 years 80% of power output

Manufacturing

- ♦ Original cell sorting system ensures the best electric cell match
- ♦ EL-Testing before packing
- ♦ Comprehensive module power testing, 100% positive output tolerance guaranteed

Performance

- ♦ Higher module efficiency and compact size.
- ♦ Weakened hot-spot effect, lower module failure rate and increased stability by shingle-tech.
- ♦ Special connection method lowers the internal resistance and ensures better performance than traditional connection with busbar.
- ♦ IP67 rated junction box, reliable cables and standard MC4 connectors improve the stability



Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C

Nominal Power	20W
Cell Type	Monocrystalline
Cell Efficiency	21.4%
Maximum Power Current (Impp)	1.01A
Maximum Power Voltage (Vmpp)	19.80V
Open-circuit Voltage (Voc)	23.40V
Short-circuit Current (Isc)	1.34A
Maximum System Voltage	1000V
Output Tolerance	+3%
Cable	No Cable
Connector Type	No Connectors
Module Structure	Aluminum Frame / Glass / EVA / Backsheet (White)
Junction box rating	≥ IP67
Number of Diodes	One
Working Temperature	-40°C ~ +80°C

Packaging

Module Dimensions	480*240*25mm
Module Weight	2.0kg
Package	Single Package
Pieces per Pallet	Free
Gross Weight per Pallet	Free
Pallet Dimensions	Free

SOLMAX NEW ENERGY B.V.
 Address: Zonnebaan 23, 3542 EB Utrecht, the Netherlands.
 Tel: +31-307 855 708
 E-mail: info@solarfam.nl

